Supplier Information  Company Name * Company Unique ID DUNS 2023-05-03  Contact Name * Title - Contact Phone - Contact * Email - Contact * Duplicate Contact -> Authorized Representative Debbie Mollner QA Customer Support Specialis 805-489-2111 dmollner @semtech.com  Authorized Representative * Title - Representative Phone - Representative * Same QA Customer Support Specialis 805-489-2111 Same  Requester Item Number Mfr Item Number Mfr Item Number Effective Date Version Manufacturing Site Weight * UOM Unit Type UCLAMP3301D.TCT Low Capacitance TVS Diode At China 5.318 mg Each  Alternate Recommendation  Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle Tin (Sn)  Alloy 42 1 260 C 30 seconds 3	ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	© Co	terial Compo pyright 2005. IPC, Bannoc nternational and Pan-Ameri	kburn, Illinois	. All rights reserv	tion with lower	level p	arts, the	declaratio	n encomp	asses all lov		terials for	which th	item is an assembly e manufacturer has eclaration.		
Company Name * Company Unique ID Unique ID Authority Response Date * Response Document ID UNIQUE ID Authority SEMTECH CORPORATION 00-847-9941 DUNS 2023-05-03  Contact Name * Title - Contact Phone - Contact * Email - Contact * dmollner @semtech.com Authorized Representative * Title - Representative Phone - Representative * Same QA Customer Support Specialis 805-489-2111 Same  Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight * UOM Unit Type UCLAMP3301D.TCT Low Capacitance TVS Diode At Alternate Recommendation Alternate Recommendation  Manufacturing Process Information  Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle Tin (Sn) Alloy 42 1 260 C 30 seconds 3	1752-2 1.1		:-1752 Standa	1752 Standard			''			eclaration Class * lass 6 - RoHS Yes/No, Homogeneous Materials and Mfg Inforr							
SEMTECH CORPORATION 00-847-9941 DUNS 2023-05-03  Contact Name * Title - Contact Phone - Contact * dmollner @semtech.com  Authorized Representative * Title - Representative Phone - Representative * Same QA Customer Support Specialis 805-489-2111 Same  Requester Item Number Mfr Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight * UOM Unit Type Alternate Recommendation   Alternate Item Comments    Manufacturing Process Information  Terminal Plating / Grid Array Material Terminal Base Alloy Alloy 42 1 Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle Number Number Number of Reflow Cycle Number Number Number Number Number of Reflow Cycle Number of Reflow Cycle Number Number Number Number Number Number Number of Reflow Cycle Number	Supplier Information																
Contact Name * Title - Contact Phone - Contact * Debbie Mollner QA Customer Support Specialis 805-489-2111	Company Name *		Company Unique ID		Unique ID Au	uthority	Respo	nse Date	*	Re	sponse Do	cument ID					
Debbie Mollner  QA Customer Support Specialis 805-489-2111  Authorized Representative * Title - Representative * QA Customer Support Specialis 805-489-2111  Requester Item Number   Mfr Item Number   Mfr Item Name   Effective Date   Version   Manufacturing Site   Weight *   UOM   Unit Type    Alternate Recommendation   Alternate Item Comments    Manufacturing Process Information  Terminal Plating / Grid Array Material   Terminal Base Alloy   Alloy 42   1  Alloy 42   1  Amouliner@semtech.com   Duplicate   Contact -> Authorized Representative    Supplier Comments or URL for Additional Information    Supplier Comments or URL for Additional Information    Meight * UOM   Unit Type    China   5.318   mg   Each    Alternate Item Comments    Manufacturing Process Information    Terminal Plating / Grid Array Material   Terminal Base Alloy   J-STD-020 MSL Rating   Peak Process Body Temperature   Max Time at Peak Temperature   Number of Reflow Cycle    Tin (Sn)   Alloy 42   1   260   C   30   seconds   3	SEMTECH CORPORATION	ON	00-847-9941		DUNS		2023-0	5-03									
Authorized Representative * Title - Representative QA Customer Support Specialis805-489-2111	Contact Name *		Title - Contact		Phone - Cor	Email	- Contac	t *		D !! .	0 1 1	Δ (1					
Same  Requester Item Number	Debbie Mollner	QA Customer Suppo	rt Speciali	li <b>s805-489-2111</b>			dmollner@semtech.com			Duplicat	e Contact	-> Autno	rizea Re	presentative			
Requester Item Number	Authorized Representative * Title - Representative				Phone - Representative *			Email - Representative *			Supplier Comments or URL for Additional Information						
China   5.318   mg   Each	Same		QA Customer Suppo	rt Speciali	<b>\$805-489-211</b>	1	Same										
Alternate Recommendation  Manufacturing Process Information  Terminal Plating / Grid Array Material	Requester Item Number	r	Mfr Item Number		Mfr Item Name	<del>)</del>	Effectiv	e Date	Version	Manufacti	uring Site	Weight *	UC	М	Unit Type		
Manufacturing Process Information       Terminal Plating / Grid Array Material     Terminal Base Alloy     J-STD-020 MSL Rating     Peak Process Body Temperature     Max Time at Peak Temperature     Number of Reflow Cycle       Tin (Sn)     Alloy 42     1     260 C     30 seconds     3			UCLAMP3301D.TCT	-	Low Capacita	ance TVS Diode A	r			China		5.318	mg		Each		
Terminal Plating / Grid Array Material  Terminal Base Alloy  Alloy 42  Terminal Base Alloy  J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle  260 C  30 seconds 3	Alternate Recommenda	ation							Alternate	Item Comi	ments	•	•		•		
Tin (Sn) Alloy 42 1 260 C 30 seconds 3	Manufacturing Proces	ss In	formation														
	Terminal Plating / Grid Array	Mater	ial	Terminal B	ase Alloy	J-STD-020 MSL Ra	ating	Peak Process Body Tempe		Temperatu	ature Max Time at Peak Ten		nperature	of Reflow Cycles			
Comments	Tin (Sn)			Alloy 42		1		260		<b>260</b> C		30 seconds		3			
Sommond	Comments					1	I.				1		ļ				

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type \*** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance \* Accepted **RoHS Declaration \*** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature** 

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

## **Homogeneous Material Composition Declaration for Electronic Products**

**Subltem Instructions:** The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

**Substance Instructions:** [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem		Homogeneous	Weight	Unit of		Level	Substance Category	tegory		Substance	CAS	Exempt	Weight	0111101	Tolerance		PPM
	Name		Material		Measure			,					•		Measure	-	+	
+1 -	Die	+M -M	Doped silicon	0.15676	8mg	+C -(	Supplier		+S	-S	Si	7440-21-3		0.156768	mg			29,476
+1	Leadframe	+M -M	Alloy 42	1.28092	2mg	+C -(	Supplier		+S	-S	Fe	7439-89-6		0.744856	mg			140,05
		_				+C -(	Supplier		+S	-S	Ni	7440-02-00		0.525178	mg			98,746
						+C -(	Supplier		+S	-S	Mn	7439-96-5		0.007685	mg			1,445.0
						+C -(	Supplier		+S	-S	Cr(not Cr 6+)	7440-47-3		0.001280	mg			240.84
						+C -(	Supplier		+S	-S	Si	7440-21-3		0.001921	mg			361.26
		+M -M	Pure silver	0.05049	2mg	+C -(	Supplier		+S	-S	Ag	7440-22-4		0.050492	mg			9,493.7
+1	Bonding wire	+M -M	1.0mil gold wire	0.02008	<b>0</b> mg	+C -(	Supplier		+S	-S	Au	7440-57-5		0.020080	mg			3,775.5
+1	Molding Compou	nd+M -M	CEL-1702HF9	3.59299	2mg	+C -(	Supplier		+S	-S	Amorphous silica1	60676-86-0		2.838464	mg			533,69
			•		•			•	+S	-s	Amorphous silica2	7631-86-9		0.287439	mg			54,045
									+S	-s	Epoxy Resin 1	Trade secre		0.179649	mg			33,778
									+S	-s	Epoxy Resin 2	Trade secre		0.071859	mg			13,511
									+S	-s	Hardener	Trade secre		0.179649	mg			33,778
									+S	-S	Catalyst	Trade secre		0.028743	mg			5,404.5
									+S	-S	Carbon black	1333-86-4		0.00718	mg			1,351.1
+1	Die attached Epo	cy+M-M	84-1LMISR4	0.06308	8mg	+C -(	Supplier		+S	-S	Silver	7440-22-4		0.048893	mg			9,193.1
		_	-						+S	-s	bisphenol-F-(epichlorh	9003-36-5		0.009463	mg			1,779.3
									+S	-s	1,4-bis(2,3 epoxypropo	2425-79-8		0.00378	mg			711.72
									+S	-s	dapsone	80-08-0		0.000946	mg			177.93
+1	Tin solder	+M -M	Pure Tin	0.15412	1mg	+C -0	Supplier		+S	-S	Sn	7440-31-5		0.154121	mg			28,978